



Super-Krete® International , Inc.

S-1700 Stamp-Kote®

Product Description

Super-Krete Stamp-Kote is a proprietary mixture of specially modified water resistant acrylic copolymer resin mixed with various sized aggregates formulated to maintain a (1/4") thickness profile that is then stamped or textured using specially designed tools and templates to achieve a simulated stone, brick or other type design. Super-Krete Color Stains are then applied over the finished stamped product to create a natural or custom colored appearance (See Spec. No S-1701 1/4" Stamp Overlay). An integral coloring may also be used. When used in the S-1701 system, Super-Krete Stamp-Kote is a unique product designed to be applied in conjunction with Super-Krete Bond-Kote® S-9300 over new or existing concrete substrates, and is a ready-mix product (add water only). See Spec. No. S-1701.

Characteristics and Advantages

- ◆ This system eliminates the need for concrete removal.
- ◆ Will simulate over 200 designs and textures.
- ◆ Available in gray and white.
- ◆ Easy to apply.
- ◆ Add water only.
- ◆ Can be used with integral colors.
- ◆ Environmentally friendly, OSHA and VOC compliant. Contains no ingredients required to be listed by OSHA 1910 1200

Uses

Interior & Exterior Floors	Malls	Pool Decks
Walkways	Pavilions	Vertical Surfaces
Stairs & Landings	Showrooms	anywhere there's concrete!
Restaurants	Driveways	

Surface Preparation

For detailed directions, see Super-Krete Surface Preparation Application Specification S-1.

Protect surrounding areas from overspray or splashes.

This product is designed to be used in conjunction with Bond-Kote S-9300 and is a wet on wet system. See the specification S-9300 on applications and instructions for Bond-Kote.

Application

For Stamp Overlay application, see Super-Krete® Specification S-1701. This product is designed to be a part of a system and is not intended to be used alone.



Super-Krete® International , Inc.

S-1700 Stamp-Kote®

Coverage Rates

**Coverage rates will vary, these are pproximations only, actual coverage will vary due to substrate conditions and surface porosity.*

Coverage rates for Super-Krete Stamp-Kote will cover approximately 25 sq. ft. per 50 lb. bag/pail at 1/4" thickness.

Cure Time

Will depend on weather.

Full cure is 7 days.

Wait 24 hours before staining.

Packaging

- Available in white and gray
- 50 lb. Bag 50 per pallet

Tools Required

- 1/4" Gauge Rake, S-19000
- Trowels
- Textured Rubber Mats

Limitations

Super-Krete products are to be applied only when surface temperatures are above 55 degrees F and rising. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

NOTE: Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.

1290 N. Johnson, Ste. 101
El Cajon, CA 92020
(619) 401-8282 P | (619) 401-8288 F | (800) 995-1716 Toll Free
www.SUPER-KRETE.com
SALES@SUPER-KRETE.com