



## Super-Krete® International, Inc.

### S-8000 Ure-Top-Kote™

#### Product Description

Super-Krete Ure-Top-Kote is a water based acrylic-urethane copolymer emulsion fortified by urethane crosslinkers to create a semi gloss, clear protective shield over Super-Krete Ure-Kote acrylic-urethane color coating and other surfaces when an extra heavy-duty surface is required. Super-Krete Ure-Top-Kote is used over concrete and masonry to produce a sealing system that penetrates the surface for a tenacious bond on interior and exterior applications where vehicular traffic IS NOT permitted.

#### Characteristics and Advantages

- ◆ Ease of application
- ◆ Performance of urethanes
- ◆ Stain resistant
- ◆ Abrasion resistant
- ◆ Easy to clean and maintain
- ◆ Durable and long lasting
- ◆ Water-based for ease of application and clean-up
- ◆ Semi Gloss
- ◆ Non-Yellowing
- ◆ Resistant to UV and weathering
- ◆ Breathes
- ◆ Won't soften
- ◆ Resistant to automotive fluids
- ◆ Resistant to many chemicals and most acids
- ◆ Environmentally friendly, OSHA and VOC compliant, Contains no ingredients required to be listed by OSHA 1910 1200

#### Uses

Super-Krete Ure-Top-Kote is used as a protective clear finish for high use applications over portland cement, masonry, wood and asphalt surfaces including:

- ◆ Natural Stone
- ◆ Stamped concrete
- ◆ Garages
- ◆ Walkways
- ◆ Kitchen Floors
- ◆ Concrete block
- ◆ Exposed aggregate
- ◆ Pre-cast concrete
- ◆ Brick
- ◆ Concrete/masonry pavers
- ◆ Pigmented cement
- ◆ Mexican pavers
- ◆ Stucco

#### Surface Preparation

***For detailed directions, see Super-Krete Surface Preparation Application Specification S-1.***

1. Open any existing cracks using a diamond crack chasing blade.
2. Remove existing dirt, grime, laitance, and debris mechanically using a blower. Shot-blasting, sand-blasting or acid washing/neutralizing should be performed to achieve a profiled surface. All surfaces to receive coatings must be profiled.
3. Clean and degrease the surface using Super-Krete Heavy Duty Degreaser.  
*For detailed directions, see Super-Krete Product Specification S-12,000 Heavy Duty Degreaser.*
4. Prepare surface using Super-Krete Pene-Krete.  
*For detailed directions, see Super-Krete Product Specification S-1300 Pene-Krete.*

Perform crack repair using the Super-Krete Application Specification S-9900 Crack Repair.



# Super-Krete® International, Inc.

## S-8000 Ure-Top-Kote™

### Application

Apply Super-Krete Ure-Top-Kote using a filtered airless sprayer, roller or hand brush. Super-Krete Ure-Top-Kote is to be used full strength. Do not dilute. Mix thoroughly with power mixer or manually prior to application.

Standard application:

1. Apply Super-Krete Ure-Top-Kote in light, even applications. Do not allow to puddle. Should puddling occur, spread immediately over surface until dissipated. Allow first application to dry thoroughly before a second application.

Note: One (1) application is normally sufficient when the substrate has been pre-coated with Super-Krete Ure-Kote. Applications over rougher or uncoated surfaces may require a second application, depending on the porosity of the surface being sealed. Best results are achieved by one person spraying and another person following with a soft bristle broom to spread the material.

#### Coverage Rates

*\*Coverage rates will vary, these are approximations only, actual coverage will vary due to substrate conditions and surface porosity.*

Super-Krete Ure-Top-Kote will cover approximately three hundred (300) sq. ft. over surfaces previously coated with Super-Krete Ure-Kote.

One (1) gallon of Ure-Top-Kote will cover approximately one hundred fifty to two hundred fifty (150-250) square feet when applied over porous surfaces. Second coat coverage will be approximately three hundred (300) square feet.

#### Cure Time

72 hours

#### Shelf Life

12 months

#### Packaging

- 1 gallon units            4 per case
- 5 gallon pails            36 per pallet
- 55 gallon drums        4 per pallet

### Limitations

Super-Krete products are to be applied only when surface temperatures are above 55 degrees F and rising. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

**NOTE: Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.**

1290 N. Johnson, Ste. 101  
 El Cajon, CA 92020  
 (619) 401-8282 P | (619) 401-8288 F | (800) 995-1716 Toll Free  
 www.SUPER-KRETE.com  
 SALES@SUPER-KRETE.com