



Super-Krete® International, Inc.

S-8200 Top Sealer™

Product Description

Super-Krete Top Sealer S-8200 is a non-toxic, surface sealer that completely seals most concrete, brick, wood and sandstone surfaces. Super-Krete Top Sealer S-8200 is highly effective and versatile in a wide range of commercial, industrial and residential applications such as stucco protection, rockscape and brick surfaces. This sealer should not be used for traffic areas.

Characteristics and Advantages

- ◆ Non-toxic, one-coat application
- ◆ Will not alter color, texture or any other physical characteristic of the surface to which it is applied.
- ◆ Retards pitting, dusting and rutting
- ◆ Leaves a clear, natural finish
- ◆ Stops seepage, dampness, molding, pitting, rutting and dusting
- ◆ Graffiti protection
- ◆ Enables easier removal of snow and ice
- ◆ Enables easy clean-up of spills or dirt with mild soap and water

For detailed directions, see Super-Krete Surface Preparation Application Specification S-1.

Super-Krete Top Sealer S-8200 is best applied to perfectly dry surfaces and in temperature conditions above 55° F. Super-Krete Top Sealer S-8200 is not meant to seal visible cracks and seal with mortar prior to application. Remove all debris, lints, dirt and coatings prior to application.

Application

1. Do not dilute or mix Super-Krete Top Sealer S-8200 with other liquid. Use as supplied.
2. Shake well before using!
3. Apply liberally and saturate all areas using a pump sprayer. On vertical walls, apply from the bottom up.
4. In areas where foreign matter such as grease or oil have penetrated below the surface, use appropriate cleaning agent Heavy Duty Degreaser, then merely allow the foreign matter to float to the surface. Flush off with water and allow to dry thoroughly. Several cleanings may be needed to rid the surface of foreign matter. Note: While the harmful oil residue will be removed, stains from used motor oil may be permanent.
5. Super-Krete Top Sealer S-8200 sets within two to four hours after applications. Limited foot traffic is permissible after 30 minutes.
6. Clean equipment with water.



Super-Krete® International, Inc.

S-8200 Top Sealer™

Coverage Rates

** Coverage rates will vary, these are approximations only, actual coverage will vary due to substrate conditions and surface porosity.*

Coverage rates for Super-Krete Top Sealer S-8200 is approximately 300 sq. ft. per gallon.

Cure Time

2-4 hours

Limited foot traffic permissible after 30 mins.

Shelf Life

Infinite

Packaging

- 1 gallon units 4 per case
- 5 gallon units 36 per pallet

Properties

Toxicity:	None
Flammability:	None
Fumes (during treatment) :	None
Organic Properties:	Negligible
Environmental Hazards:	None
Diluent:	Use as supplied

Caution

Do not allow Super-Krete Top Sealer S-8200 to puddle.

Do not apply to glass, glazed surfaces or aluminum as etching will occur. In case of accidental contact, rinse thoroughly with water immediately. If second application is required, immediately remove excess with a dry roller or by other means.

Do not apply to uncured or previously sealed asphalt. Super-Krete Top Sealer S-8200 is not meant to fill or seal visible cracks.

A test sample is always recommended prior to application.

Limitations

Super-Krete products are to be applied only when surface temperatures are above 55 degrees F and rising. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

NOTE: Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.

1290 N. Johnson, Ste. 101
El Cajon, CA 92020
(619) 401-8282 P | (619) 401-8288 F | (800) 995-1716 Toll Free
www.SUPER-KRETE.com
SALES@SUPER-KRETE.com