



Product Description

Super-Krete Ure-Kote is a single component, water based, acrylic/urethane paint formulated for use in heavy traffic areas and designed to withstand heavy foot and tire traffic. Super-Krete Ure-Kote is water and petroleum resistant. Available in a variety of colors (see Super-Krete Color Palette), uses range from heavy use areas such as roads, bridges and parking lots to recreational surfaces such as roller-blade rinks, basketball and tennis courts. Super-Krete Ure-Kote is to be applied over asphalt or any surface that has been pre-coated with Super-Krete Bond-Kote.

Characteristics and Advantages

- Resists Wear
- Stain , Petroleum and Water Resistant
- Non-hazardous
- Multi-Use Product
- Easy to Maintain
- Resists UV Rays
- Environmentally Friendly
- Available in 16 Colors

Uses

- Interior/Exterior Applications
- Recreational and Decorative Surfaces
- Pool Decks, Driveways and Patios
- Skid Resistance
- Striping Paint
- Game Court Surfaces

Surface Preparation

For detailed directions, see Super-Krete Surface Preparation Application Specification S-1.

1. Open any existing cracks using a diamond crack chasing blade.
2. Remove existing dirt, grime, laitance, and debris mechanically using a blower. Shot-blasting, sand-blasting or acid washing/neutralizing should be performed to achieve a profiled surface. All surfaces to receive coatings must be profiled.
3. Clean and degrease the surface using Super-Krete Heavy Duty Degreaser.
For detailed directions, see Super-Krete Product Specification S-12,000 Heavy Duty Degreaser.
4. Prepare surface using Super-Krete Pene-Krete.
For detailed directions, see Super-Krete Product Specification S-1300 Pene-Krete.

Perform crack repair using the Super-Krete Application Specification S-9900 Crack Repair.

Mixing

Super-Krete Ure-Kote should always be mixed prior to use. Suitable mixing equipment includes jiffy mixers, motor mixers, seal coat machinery or bulk slurry type machinery depending upon job size. Up to five (5) pounds of aggregate will determine the degree of slip resistance or texture.

Application Equipment

Super-Krete Ure-Kote may be applied by many types of equipment including:

- ?? Roller
- ?? Squeegee, Sprayer or Brush

Application

Do not pre-dampen the surface. Blistering may occur if Super-Krete Ure-Kote is applied over a wet surface. Normal application is two (2) coats. Rough or pitted areas may require additional applications. Up to five (5) pounds of fine silica sand may be mixed into each gallon of Super-Krete Ure-Kote for filling or smoothing.



Super-Krete® International, Inc.

S-11,000 Ure-Kote™

Coverage Rates

** Coverage rates will vary, these are approximations only, actual coverage will vary due to substrate conditions and surface porosity.*

200 sq. ft. / gallon
Two coats recommended

Cure Time

Applications of Super-Krete Ure-Kote will normally dry to foot traffic within one (1) hour in warm, dry temperatures. Drying time in shaded areas or on cool, damp days will be longer. Darker colors dry faster than light colors. For best results, allow surface to warm up prior to application. Longer cure times prior to traffic assure better results.

Shelf Life

12 months

Packaging

- 1 gallon bottles 4 per case
- 5 gallon pails 36 per pallet
- 55 gallon drums 4 per pallet

Limitations

Super-Krete products are to be applied only when surface temperatures are above 55 degrees F and rising. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

NOTE: Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.

1290 N. Johnson, Ste. 101
El Cajon, CA 92020
(619) 401-8282 P | (619) 401-8288 F | (800) 995-1716 Toll Free
www.SUPER-KRETE.com
SALES@SUPER-KRETE.com