
SUPER-KRETE products and systems are warranted only when applied by persons Certified in writing by Super-Krete International, Inc. as Certified Super-Krete Applicators in accordance with manufacturer's guidelines on a structurally sound surface.

Description

SUPER-KRETE LIQUID RELEASE AGENT is a product formulated for use with the Super-Krete STAMP-KOTE system and is to be used as a parting agent in conjunction with Super-Krete Texturing Mats (available in various patterns). Liquid Release prevents mats from sticking to STAMP-KOTE and forms a lubricated barrier between the mat and the surface. Liquid Release also provides protection to the texturing mats and increases their life span by decreasing the friction caused by stamping surfaces.

Uses

SUPER-KRETE LIQUID RELEASE AGENT is formulated to be used with most texturing mats, however, a test prior to use on texturing mats other than those by SUPER-KRETE is always recommended to insure compatibility.

Application

Liberal apply a mist of Liquid Release onto STAMP-KOTE where you are going to place the texturing mats. Do not apply over an area of more than ten or fifteen square feet as the product may evaporate before the mats are placed over it. Also spray the texturing mats for enhanced lubrication prior to stamping the STAMP-KOTE.

For more information Stamped Concrete Overlays, please see SUPER-KRETE Specification No. S-1701, STAMP-KOTE Application System.

To maintain the integrity of the concrete/Stamp-Kote surface, do not trowel or in any way mix the Super-Krete Liquid Release with the surface. To make corrections on the still plastic concrete, use the texturing mat and press out the unwanted impression. No removal of the Liquid Release is necessary. When the texturing application is complete, wash off the Liquid Release from the texturing mats, using plain water and soap.

IMPORTANT NOTE: Application is by Certified Applicators only. The Super-Krete's S-1701 system shall only be applied by applicators who are certified in writing by SUPER-KRETE International, Inc. to install this system. Super-Krete products are only warranted when applied by approved and certified applicators.

Limitations

SUPER-KRETE products are to be applied only when surface temperatures are above 55 degrees F and rising. SUPER-KRETE products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

Note: SUPER-KRETE International, Inc. warrants this product to be of merchantable quality when used or applied by professional applicators approved by this company in strict accordance with manufacturer's specifications. SUPER-KRETE International, Inc. does not warrant this product for uses other than those intended. SUPER-KRETE International, Inc. does not make nor does it authorize any agent or representative to make any other warranty of MERCHANTABILITY OR FITNESS for purpose or any warranty, guarantee, or representation, express or implied, concerning this material except that it conforms to product specifications distributed by this company. SUPER-KRETE believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied, is made as to the effect of such use and no liability is assumed, directly or indirectly, from their use. Buyers and users accept this product under these conditions and assume the risk of any failure, injury, to person or property (including of buyer and user), death, loss or liability resulting from the handling, storage, or use of the product whether or not it is handled, stored, or used in accordance with directions or specifications. Any liability of this company to the buyer or user of this product is limited to the replacement value of the product. Buyers and users are encouraged to conduct their own test prior to application.