
SUPER-KRETE products and systems are warranted only when applied by persons Certified in writing by Super-Krete International, Inc. as Certified Super-Krete Applicators in accordance with manufacturer's guidelines on a structurally sound surface.

DESCRIPTION AND USES

Super-Krete TOP SEALER is a non-toxic, surface sealer that completely seals most concrete, brick, wood and sandstone surfaces. Super-Krete TOP SEALER is highly effective and versatile in a wide range of commercial, industrial and residential applications such as stucco protection, rockscape and brick surfaces.

Super-Krete TOP SEALER will not alter color, texture or any other physical characteristic of the surface to which it is applied. It leaves a clear, natural finish.

Super-Krete TOP SEALER stops seepage, dampness, molding, pitting, rutting and dusting.

Super-Krete TOP SEALER can be used for graffiti protection.

Super-Krete TOP SEALER enables easier removal of snow and ice and easy clean-up of spills or dirt with mild soap and water.

SURFACE PREPARATION

*See Super-Krete Application Specification NO. S-1 Surface Preparation

APPLICATION

Do not dilute or mix Super-Krete TOP SEALER with other liquid. Use as supplied. Apply using brush or pump type sprayer.

SHAKE WELL BEFORE USING! Apply liberally and saturate all areas.

On vertical walls, apply from the bottom up. In areas where foreign matter such as grease or oil have penetrated below the surface, use appropriate cleaning agent Heavy Duty Degreaser, then merely allow the foreign matter to float to the surface. Flush off with water and allow to dry thoroughly. Several cleanings may be needed to rid the surface of foreign matter.

Note: While the harmful oil residue will be removed, stains from used motor oil may be permanent.

Super-Krete TOP SEALER sets within two to four hours after applications. Limited foot traffic is permissible after 30 minutes.

CAUTION:

Do not allow Super-Krete TOP SEALER to puddle. Do not apply to glass, glazed surfaces or aluminum as etching will occur. In case of accidental contact, rinse thoroughly with water immediately.

If second application is required, immediately remove excess with a dry roller or other means. Do not allow to puddle and dry.

Do not apply to uncured or previously sealed asphalt.

Super-Krete TOP SEALER is not meant to fill or seal visible cracks.

For surfaces not specified, we recommend that Super-Krete® TOP SEALER be applied to a small test area first.

If Super-Krete TOP SEALER is frozen, thaw out completely before using. Freezing will not harm the product.

Limitations

SUPER-KRETE products are to be applied only when surface temperatures are above 55 degrees F and rising. SUPER-KRETE products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

Note: SUPER-KRETE International, Inc. warrants this product to be of merchantable quality when used or applied by professional applicators approved by this company in strict accordance with manufacturer's specifications. SUPER-KRETE International, Inc. does not warrant this product for uses other than those intended. SUPER-KRETE International, Inc. does not make nor does it authorize any agent or representative to make any other warranty of MERCHANTABILITY OR FITNESS for purpose or any warranty, guarantee, or representation, express or implied, concerning this material except that it conforms to product specifications distributed by this company. SUPER-KRETE International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied, is made as to the effect of such use and no liability is assumed, directly or indirectly, from their use. Buyers and users accept this product under these conditions and assume the risk of any failure, injury, to person or property (including of buyer and user), death, loss or liability resulting from the handling, storage, or use of the product whether or not it is handled, stored, or used in accordance with directions or specifications. Any liability of this company to the buyer or user of this product is limited to the replacement value of the product. Buyers and users are encouraged to conduct their own test prior to application.