



Super-Krete® International, Inc.

S-9400 Pool Texture™

Product Description

Super-Krete™ Pool Texture is a proprietary mixture of specially modified water resistant acrylic copolymer resin mixed with various sized aggregates. Super-Krete™ Pool Texture is designed to be applied with a hopper gun to achieve a spray texture finish and knocked down with a trowel or can be left free standing. Super-Krete™ Pool Texture is designed for use as a decorative finish over Super-Krete™ Bond-Kote.

Characteristics and Advantages

- Increased skid resistance
- High Coefficient of Friction
- Cooler pool decks
- Eliminates concrete removal
- Resistant to UV rays
- Penetrates for a tenacious bond
- Ease of application (Add water only)
- Easy to maintain
- Environmentally friendly, VOC compliant
- Non-Toxic, and OSHA Compliant

Uses

- Exterior Floors
- Malls
- Walkways
- Driveways
- Pavilions
- Pool Decks
- Stairs and Landings
- Patios and Decks
- Vertical Surfaces
- Interior and Exterior Walls

Surface Preparation

For detailed directions, see Super-Krete Surface Preparation Application Specification S-1.

1. Open any existing cracks using a diamond crack chasing blade.
2. Remove existing dirt, grime, laitance, and debris mechanically using a blower. Shot-blasting, sand-blasting or acid washing/neutralizing should be performed to achieve a profiled surface. All surfaces to receive coatings must be profiled.
3. Clean and degrease the surface using Super-Krete Heavy Duty Degreaser.
For detailed directions, see Super-Krete Product Specification S-12,000 Heavy Duty Degreaser.
4. Prepare surface using Super-Krete Pene-Krete
For detailed directions, see Super-Krete Product Specification S-1300 Pene-Krete.
Perform crack repair using the Super-Krete Application Specification S-9900 Crack Repair.

Application

Super-Krete Pool Texture is applied by hopper gun.

Product Mixing: Mix, with a “Jiffy” mixer in a 5 gallon bucket, 4-6 quarts of clean water to 1 bag of Super-Krete Pool Texture until desired consistency is achieved.

1. Using a hopper gun and air compressor on low pressure (15-18 lbs). Apply with the largest opening spray apparatus.
2. Knock down Super-Krete™ Pool Texture with a trowel.

Coverage Rates

**Coverage rates will vary, these are approximations only, actual coverage will vary due to substrate conditions and surface porosity.*

175 sq. ft. / bag

Shelf Life

N/A, Must be stored in dry area.

Packaging

- 50 lb. bags 50 per pallet

Dry Time

.5 an hour to one hour Full Cure: 72 hours

Appearance

Gray powdered form

Limitations

Super-Krete products are to be applied only when surface temperatures are above 55 degrees F and rising. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

NOTE: Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.

1290 N. Johnson, Ste. 101
 El Cajon, CA 92020
 (619) 401-8282 P | (619) 401-8288 F | (800) 995-1716 Toll Free
 www.SUPER-KRETE.com
 SALES@SUPER-KRETE.com