

**SUPER-KRETE products and systems are warranted only when applied by persons Certified in writing by Super-Krete International, Inc. as Certified Super-Krete Applicators in accordance with manufacturer's guidelines on a structurally sound surface.**

## Description

Super-Krete COLOR STAIN is a multi-purpose, spray applied, penetrating acrylic-urethane copolymer sealer. Color Stain is available in a variety of standard pigmented colors and can be custom tinted to almost any color. It is used as protective, decorative sealing systems over pigmented and unpigmented Super-Krete surfaces, concrete, masonry and wood surfaces.

## Advantages

- Helps prevent staining
- A waterproofing agent
- Resistant to ultraviolet rays
- Durable, long lasting
- Easy to maintain
- Environmentally friendly, OSHA approved

## Preparation of Surface

New or un-coated surfaces shall be degreased to remove all grease, oil and grime from the substrate. The surface shall also be cleaned using Super-Krete® Heavy Duty Degreaser. Allow the degreaser to dwell on the surface for a minimum of fifteen (15) minutes and then rinse with clean water. The surface may require at least two (2) etchings and rinses with cleaner/degreaser to achieve the same results. For best results, use minimum 3000 psi pressure washer.

## Application

Surface to be stained and/or sealed shall be completely cured and dry prior to application. Use COLOR STAIN full strength; do not dilute. Mix with jiffy mixer or manually prior to use. Apply first application using an airless paint spraying machine or hand pump sprayer. Do not allow the product to puddle. Should puddling occur, immediately spread or thin material using a soft bristle broom. When dry, apply the second coat following the same application procedure used on the first coat. If using to stain stamped concrete or Super-Krete Stamp-Kote® you can spray light mist of water to model the color stain.

## Coverage

Theoretical coverage is 300 square feet per gallon for two coats, depending on surface porosity. Coverage rate will improve substantially with each additional application.

## COLOR STAIN Curing Time

COLOR STAIN dries quickly (15-30 minutes). Foot traffic is permitted one hour after completion of application. Note: No vehicular traffic should be permitted until final cure, which will be 72 hours, depending on weather conditions and temperatures.

## Uses

Typical applications include coloring and sealing of substrates such as:

- Driveways
- Pebble Stone
- Exposed Aggregate
- Stucco
- Pre-cast Concrete
- Natural Stone
- Pool Decks
- Walkways
- Brick
- Wood Decks
- Stamped Concrete
- Interlocking Pavers
- Tile

Note: Apply Super-Krete products only when surface temperature is above 55 degrees F. and rising. Do not apply when rain or other precipitation is expected within 24 hours.

## Color Selection

Color Stain is available in a variety of colors (see Standard Color Chart).

## **Safety**

COLOR STAIN are environmentally friendly and contain no ingredients which are required to be listed by OSHA per 29 CFR 1910.1200. Material Safety Data Sheets are available upon request.

**IMPORTANT NOTE:** Application is by Certified Applicators only. The Super-Krete S-9500 system shall only be applied by applicators who are certified in writing by SUPER-KRETE® International, Inc. to install this system. Super-Krete products are only warranted when applied by approved and certified applicators.

## **Limitations**

SUPER-KRETE products are to be applied only when surface temperatures are above 55 degrees F and rising. SUPER-KRETE products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze.

Note: SUPER-KRETE International, Inc. warrants this product to be of merchantable quality when used or applied by professional applicators approved by this company in strict accordance with manufacturer's specifications. SUPER-KRETE International, Inc. does not warrant this product for uses other than those intended. SUPER-KRETE International, Inc. does not make nor does it authorize any agent or representative to make any other warranty of MERCHANTABILITY OR FITNESS for purpose or any warranty, guarantee, or representation, express or implied, concerning this material except that it conforms to product specifications distributed by this company. SUPER-KRETE believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied, is made as to the effect of such use and no liability is assumed, directly or indirectly, from their use. Buyers and users accept this product under these conditions and assume the risk of any failure, injury, to person or property (including of buyer and user), death, loss or liability resulting from the handling, storage, or use of the product whether or not it is handled, stored, or used in accordance with directions or specifications. Any liability of this company to the buyer or user of this product is limited to the replacement value of the product. Buyers and users are encouraged to conduct their own test prior to application.