

*Slip*NOT® CURRENT SPECIFICATIONS

SlipNOT® CURRENT SPECIFICATIONS TO SPECIFY:

STEEL

SlipNOT® anti-slip, non-gritted, steel **Grip Plate®/Grip Grate® Grade #2 - Medium**, as manufactured by **W.S. Molnar Company (1-800-SlipNOT)** in sizes and thickness as shown on drawings. Steel Grip Plate®/Grip Grate® shall incorporate an anti-slip primarily martensitic steel surface covering 100% of substrate consisting of a random hatch matrix with a surface hardness of at least 55 on the Rockwell "C" scale and a bond strength to the Grip Plate®/Grip Grate® of at least 4,000 psi. The anti-slip surface shall have a minimum coefficient of friction of 0.6 and be listed as slip resistant by Underwriters Laboratories.

STAINLESS STEEL

SlipNOT® anti-slip, non-gritted, stainless steel **Grip Plate®/Grip Grate® Grade #2 - Medium**, as manufactured by the **W. S. Molnar Company (1-800-SlipNOT)** in sizes and thickness as shown on drawings. Stainless steel Grip Plate®/Grip Grate® shall incorporate an anti-slip stainless steel surface covering 100% of substrate consisting of a random hatch matrix with a surface hardness of at least 55 on the Rockwell "C" scale and a bond strength to the Grip Plate®/Grip Grate® of at least 4,000 psi. The anti-slip surface shall have a minimum coefficient of friction of 0.6 and be listed as slip resistant by Underwriters Laboratories.

ALUMINUM

SlipNOT® anti-slip, aluminum **Grip Plate®/Grip Grate® Grade #2 - Medium**, as manufactured by **W.S. Molnar Company (1-800-SlipNOT)** in sizes and thickness as shown on drawings. Aluminum Grip Plate®/Grip Grate® shall incorporate an anti-slip aluminum surface covering 100% of substrate consisting of a random hatch matrix and a bond strength to the Grip Plate®/Grip Grate® of at least 2,000 psi. The anti-slip surface shall have a minimum coefficient of friction of 0.6 and be listed as slip resistant by Underwriters Laboratories

***Slip*NOT®**
Metal Safety Flooring

DIVISION OF THE W. S. MOLNAR COMPANY

For more information please contact us at:

2545 Beaufait St., Detroit, MI 48207

phone: (313) 923-0400 fax: (313) 923-4555

www.slipnot.com / info@slipnot.com / 800-SLIPNOT