



MCR 139-A



EL 462-A



ETF 492-A



ETF 458-A



EL 154



AC-11

# MICROPlumb® PRODUCTS Infrared Shower Control

# MCR 215

## ► Description


Infrared sensor-activated, electronic shower control for a single, pre-mixed shower. System includes six components: ETF 492-A, EL 154, MCR 139-A, ETF 458-A, EL 462-A and AC-11.

## ► Specifications

- Infrared sensor module, controller, solenoid, 120 VAC/24 VAC transformer, 20' power cord kit and mounting hardware for sensor and controller
- Water-proof (NEMA 6) sensor module
- Operates on 24 VAC
- Visible LED target detection
- Adjustable sensing range
- Adjustable run time
- 24 VAC brass body solenoid with integral "Y" strainer
- Diagnostic LED indicators in control module
- Control module may be located remotely as far as 35' from sensor using additional MICROPlumb® extension cord kits
- RJ-11 modular connections from sensor and solenoid to controller
- AC-11 Act-O-Matic® self-cleaning shower head with thumb screw volume control

## ► Accessories

- ETF 1003-72 6' Single Wire Extension Cord Kit
- ETF 1003-108 9' Single Wire Extension Cord Kit
- ETF 1003-240 20' Single Wire Extension Cord Kit



This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.



10500 Seymour Avenue • Franklin Park, Illinois 60131-1259  
Phone 800-671-6970 • Fax 847-671-6944